

IMPROVED METHOD FOR FILTERING A LIQUID METAL ON A
BED OF REFRACTORY PARTICULATE MATERIAL

Technical field
Field of the Invention

The invention relates to an improved method for filtering a liquid metal, in particular aluminium, magnesium, or their alloys on a thick bed of refractory gravel.

5 Description of Related Art
State of the art

The filtering of liquid aluminium on a thick bed of gravel made of sintered alumina, so-called tabular alumina which is an alpha alumina, generally in the form of beads or crushed grains, is known, for removing solid or liquid inclusions from it. It is very important to be able to improve this removal in particular when aluminium is used for obtaining very thin sheets in order to reduce the risk of waste material; indeed, the thinner the produced sheet, the more it becomes necessary to remove the small sized inclusions, in addition to the large ones, because they produce defects which become detrimental.

The bed of sintered alumina gravel generally has a thickness of the order of 40 cm. The purification rate of liquid metal after filtering inclusions by this type of alumina is limited; thus said metal may further contain after filtration up to 10,000 particles of a size greater than 20 μm per kg, even for a residence time which generally is between 100 and 500 secs, wherein said purification rate is very variable depending on the size of the particles and from one casting operation to another. Furthermore, it should be noted that this type of alumina is expensive.

The applicant has thus tried to reduce the amount of inclusions present in the filtered liquid metal by more particularly concerning herself with improving the removal of small size inclusions. She has also tried to reduce the cost, and more generally improve the performances of the liquid metal filtering process through a bed of particulate material, while trying to find a solution to the problem of recycling said bed of particulate material.

10 SUMMARY OF THE INVENTION
Description of the invention

The invention is a method for filtering a liquid metal wherein said liquid metal flows through a thick bed of refractory particulate material having an open porosity between 5 and 30%.

This method is essentially applied to aluminium, magnesium or their alloys.

Porosity, which corresponds to the porous volume of the grains of the bed (surface porosities and internal porosities) is measured by mercury porosimetry; it is due to pores of a diameter essentially greater than 10 μm and generally less than 200 μm in order to maintain good resistance to erosion. The particle size is preferably between 0,2 and 20 mm and the bed has a thickness of 4 to 40 cm. The residence time of the liquid metal in the gravel bed may be of the same order of magnitude as that used for the tabular alumina gravel but it is remarkable to note that a purification, at least equivalent, or even superior, to that obtained with said alumina, is obtained for residence times less than 200 secs, or even less than 50 secs. With such short residence times, the size of the industrial facilities may be

significantly reduced, while maintaining a same filtration efficiency.

As a comparison, tabular alumina gravel has a very low porosity generally less than 3% due to very fine pores less than 10 μm in majority.

The material used in the invention advantageously is an alumina. According to the preferred embodiment of the invention, said refractory material is an electrofused corundum obtained by fusing an alumina in an arc oven, followed by a casting process, preferably in moulds, by adjusting the cooling and solidification state in order to obtain the desired open porosity, and by a crushing and/or grinding process, for example in a roller or hammer mill, wherein the obtained gravel is then screened to the desired size and dust removed. Crystallization modifiers such as F, B, Y, MgO or SiO₂ may be added for controlling the porosity. Preferably, white corundum is used in order to prevent any risk of chemically contaminating the liquid metal.

The removal rate of the inclusions is always greater than 95%, even greater than 97%, regardless of the size of said inclusions, which also results in a significant reduction in the presence of particles with small dimensions.

It is important to note that even if it is always possible to use a long residence time in order to improve the removal rate of the inclusions, with the invention reduced residence times may be used while maintaining a quality level at least equal, or even superior to that observed with other particulate materials and a remarkable constancy from one casting process to another, which for example is not the case with tabular alumina. The possibility of filtering with

reduced residence times also results in a given thickness of the gravels, by the possibility of increasing the metal flow rate (or the filtration rate) with equal efficiency. This possibility may also limit the release of inclusions during surges of the metal flow rate.

Thus, the residence time may be as reduced as 1 sec, preferably at least 2 secs, and still preferably at least equal to 5 secs; it is generally less than 500 secs, preferably less than 200 secs, and preferably still less than 100 secs, and is advantageously located between 2 and 200 secs or better between 2 and 100 secs, or even between 5 and 100 secs, the shortest residence times being determined by the level of the desired removal rate and the accepted risk of release of the inclusions.

As an illustration, the number of particles present in the filtered metal does not generally exceed 600 particles with a size greater than 20 μm per kg of filtered liquid metal, the amount of smaller particles being reduced by the same factor. It appears that not only the fixing of the inclusions is better carried out but even that no release occurs.

It seems that the presence of the required minimum porosity plays a primordial role for increasing the filtration efficiency, the retention rate for the inclusions, the filtration rate, or for reducing the size of retained inclusions and for preventing their release.

Also, the retention capacity of the inclusions in corundum is larger than in tabular alumina, i.e., at a constant purification rate of the liquid metal, the lifetime of the filters is increased. The frequency of

2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2689 2690 2691 2692 2693 2694 2695 2696 2697 2698 2699 2700 2701 2702 2703 2704 2705 2706 2707 2708 2709 2710 2711 2712 2713 2714 2715 2716 2717 2718 2719 2720 2721 2722 2723 2724 2725 2726 2727 2728 2729 2730 2731 2732 2733 2734 2735 2736 2737 2738 2739 2740 2741 2742 2743 2744 2745 2746 2747 2748 2749 2750 2751 2752 2753 2754 2755 2756 2757 2758 2759 2760 2761 2762 2763 2764 2765 2766 2767 2768 2769 2770 2771 2772 2773 2774 2775 2776 2777 2778 2779 2780 2781 2782 2783 2784 2785 2786 2787 2788 2789 2790 2791 2792 2793 2794 2795 2796 2797 2798 2799 2800 2801 2802 2803 2804 2805 2806 2807 2808 2809 2810 2811 2812 2813 2814 2815 2816 2817 2

The fact of being able to use high filtration rates while improving the purification rate and retention rate may increase productivity, reduce the size of filtering facilities, reduce consumption of filtering medium and thus obtain a reduction in costs all the more significant as corundum is itself less expensive than tabular alumina.

30 Said bed may optionally be reinforced in order to
facilitate its handling.

Handwritten signature

Two filtering beds were successively used in the same facility for performing several castings each.

The first bed, according to the prior art, is based on tabular alumina beads with a particle size of 3/6 mesh, i.e. between 3.35 mm and 6.70 mm, and with a porosity of 2.8% mostly due to pores with a diameter less than 7 μm ; it has a thickness of 40 cm. Measurement of the specific surface, according to the multi-molecular adsorption measurement method known as the BET (Brunauer, Emmet and Teller) method, gave a value of 0.012 m^2/g for this bed.

The second bed, according to the invention, is a white corundum (with a purity higher than 99.6%) with porosity of 10.7% mostly due to pores with a diameter between 10 and 250 μm , its particle size is between 3 and 6 mm and the bed has a thickness of 40 cm. It is obtained by casting liquid alumina into metal ingot moulds, wherein the cooling and solidification rate is 50 to 100°C/hr, by crushing the solidified product and then grinding it in a roller mill and by screening it between sieves with 3 and 6 mm apertures. The BET specific surface of this bed was 0.09 m^2/g . The particles of the bed were rather of an acicular shape, even needle-shaped in certain tests.

The porosity distribution of the bed's particles according to the prior art (curve A) and according to the invention (curve B) is illustrated in Fig. 1. Fig. 1a gives the porous volume V (in cm^3/g) versus the pore diameter \varnothing (in μm). Fig. 1b gives the same pore distributions as Fig. 1a in cumulative form (cumulative pore distributions).

The liquid metal used is an aluminium-magnesium alloy (1.2%) wherein known additions of inclusions with

a size less than 120 μm were made in order to obtain between 10,000 and 35,000 inclusions/kg of metal depending on the castings. The residence time of liquid aluminium in the filtering bed is 100 secs during each of the castings.

Counting of the inclusions is carried out by means of a LiMCA (Liquid Metal Cleanliness Analysis) apparatus marketed by BOMEM and implementing in liquid aluminium the well-known counting method of the so-called Counter Coulter type which measures both number and size of the particles by measuring electric resistance when the latter pass through a calibrated port.

The tables below give for each casting, the inclusion removal rate, in %, observed during the casting depending on the size of the inclusions. Table 1 corresponds to tests according to the prior art, Table 2 corresponds to the tests according to the invention.

Table 1: Inclusion removal rate after filtration on a tabular alumina bed (comparative tests)

Inclusion size μm	20-40	40-60	60-80	>80
Casting 1	77	73	77	87
Casting 2	95	93	91	94
Casting 5	88	90	87	92
Casting 6	84	90	92	98
Average	86	87	87	93

It is seen that in these tests, dispersion of the results is significant both from one casting to another and depending on the particle size and that on average,

removal rate is insufficient as it does not exceed 93% for the largest inclusions. The randomness of the inclusion removal rate is particularly detrimental because it considerably increases the risk of waste material when thin or very thin metal sheets are obtained subsequently.

Table 2: Inclusion removal rate after filtration on a corundum bed according to the invention

Inclusion size μm	20-40	40-60	60-80	80-100
Casting 1	98	99	98	97
Casting 2	99	99	100	99
Casting 3	98	98	96	99
Casting 4	99	99	99	98
Casting 5	99	99	98	97
Average	99	99	98	98

It is observed that the filtering result is both excellent in homogeneity and in level as the removal rate is on average at least 98%. In particular, the smallest particles have been very well removed.

Fig. 2, which gives the filtration efficiency E (in %) versus the residence time T (in seconds) for a filter according to the prior art (curve A) and according to the invention (curve B), shows that filtering beds according to the invention maintain a very high filtering efficiency for residence times less than 200 secs, whereas the efficiency of filtering beds of the prior art are substantially reduced for residence times less than 200 secs. The residence time corresponds to the equivalent drum-vacuum filtering

rate, i.e. it corresponds to the minimum residence time
calculated from the metal flow rate as if it were a
laminar flow. In spite of a close, even lower specific
surface than that of the bed of the prior art, the bed
5 according to the invention did exhibit larger
filtration efficiency.

05030460 000704
10/000 09495950